


Summary

- A one-parameter critical gradient model is considered for island stabilization by localized heating
- It is characterized by profile stiffness, expected to be about 8 in ITER [5]
- Investigation of a critical temperature gradient model on ECRH/ECCD RF-efficiency
 - Derivation of a modified Rutherford Equation adding RF-power contribution
 - Stabilization efficiency by RF-current and -power on an ITER-like equilibrium
- Driving a (3/2) NTM magnetic island to saturation for an ITER-like plasma
- Island control by ECRH and ECCD XTOR-2F full MHD code [2,4]
- The NTM drive is affected by the ECRH and has to be taken into account while yet it is neglected in the model

Stiffness Model

- Turbulent transport has thresholds due to critical temperature gradient [1,3]
- Heat flux $q_{\perp} = -N\chi_{\perp}\nabla T$
- Diffusion coefficient χ_{\perp} modeled as $\chi_{\perp} = \chi_{\perp 0} \left| \frac{\nabla T}{\nabla T_{eq}} \right|^{\sigma-1}$
- 1 parameter model: stiffness σ**

Modified Rutherford Equation (MRE) With RF-Current (I_{RF}) and -Power (P_{RF}) Driven by ECCD


- MRE taking into account the Ohmic contribution $a\Delta'_{\Omega}$
- Effect of P_{RF} while J_{RF} acts as
- No P_{RF} effects on the bootstrap current due to symmetry

$$0.82S_0 \frac{dW}{dt} = a\Delta' + a\Delta'_{\Omega} + C_{bs}J_{bs}W - C_{RF}I_{RF} \frac{\eta_{RF}}{W^2}$$

- The contribution of the power has stabilizing effect when modulated at the 'O'-point [6,7]
- A contribution to the MRE is derived for the stiffness parameter
- Here μ_c corresponds to the RF-power deposition location within the magnetic island

$$a\Delta'_{\Omega} = -\mathcal{F}_{\Omega} \left(\mu_c, \frac{P_{RF}^{tot}}{P_{eq}}, \sigma \right) \frac{a q \mu_0 R J_{\Omega}}{J s B_z} \frac{P_{eq}}{N\chi_{\perp 0}^2 T_s}$$


- As long as $\nabla T < \nabla T_{eq}$ for $P_{RF}/P_{eq} < 1$, χ_{\perp} remains low inside the island. As a consequence, the RF-power stabilization is enhanced for perfect 'O'-point heating (modulation)




ITER-like equilibrium

- As an application for our model, we take an ITER-like equilibrium
- Scenario Q=10, plasma current $I_p = 15$ MA
- RF-current injection for control $I_{RF} = 0.8\% I_p$
- RF-power for island control $P_{RF} = 13$ MW


(3/2) Neoclassical Island




- The bootstrap current (I_{bs}) is the drive that made the island growth
- A threshold exist under which the magnetic island is stable
- The ω^* effects are stabilizing




Modulation cycle for modulated driven RF-current (I_{RF}) at a frequency of 10Hz



- The RF-efficiency is slightly affected by the stiffness when only RF-current (I_{RF}) is driven



- The RF-efficiency is largely enhanced driving RF-current (I_{RF}) and power (P_{RF}) inside the magnetic island



- RF-efficiency is averaged at each RF-cycles from the half-high to the maximum.
- RF-power enhances the RF-efficiency for both a stiffness of 1 and 8


Numerical aspects, ECCD/ECRH Governing Equations

- The XTOR-2F contains an RF-current and -power source [2,4]
- Propagation of RF-current along field lines through parallel diffusion are verified [2]

$$\frac{\partial J_{RF}}{\partial t} = \nu_f (J_s - J_{RF}) + \chi_{\perp}^{RF} \nabla^2 J_{RF} + \chi_{\parallel}^{RF} \nabla_{\parallel}^2 J_{RF}$$



$$\frac{\partial P_{RF}}{\partial t} = \nu_f (P_s - P_{RF}) + \chi_{\perp}^{RF} \nabla^2 P_{RF} + \chi_{\parallel}^{RF} \nabla_{\parallel}^2 P_{RF}$$

- Index s stands for source which is implemented as a 1D or 3D one
- Note that the sources used in simulations are 1D except for modulation which are 3D



(3/2) Neoclassical Tearing Mode Control driving RF-Current and Power

- Driving RF-current in addition with RF-power results in a large decrease of the island size for a short time period
- Large stiffness is apparently less favorable




- No effect of the stiffness on the RF-current (I_{RF}) injection
- Injection of RF-power (P_{RF}) seems to be efficient only during about 200 τ_A for the case $\sigma = 8$

Conclusion and Outlooks

- Adding RF-power (P_{RF}) to the RF-current (I_{RF}) enhances the RF-efficiency
- In presence of stiffness, it seems that driving RF-power (P_{RF}) is less effective even for modulation control scheme
- Possible explanation is the effect of the bootstrap current (I_{bs}) since the magnetic island is not perfectly symmetric $I_{RF} = 0.8\% I_p$ and P_{RF}

- C_{Jbs} is the contribution of the bootstrap current to the island current
 - The stiffness has an non-negligible effect on the bootstrap current and heating acts on the equilibrium bootstrap



References

- M. Romanelli, C. Bourdelle, and W. Dorland, Physics of Plasmas, 11, 3845 (2004)
- O. Février, P. Maget, H. Lütjens, et al., Plasma Physics and Controlled Fusion, 58, 045015 (2016)
- F. Imbeaux, F. Rytter, and X. Garbet, Plasma Physics and Controlled Fusion, 43, 1503 (2001)
- H. Lütjens, and J.-F. Luciani, Journal of Computational Physics 229, 8130 (2010)
- J.E. Kinsey, et al., Nuclear Fusion, 51, 083001 (2011)
- C.C. Hegna, and J. D. Callen, Physics of Plasmas, 4, 2940 (1997)
- D. D. Lazzari and E. Westerhof, Nuclear Fusion, 49, 075002, (2009)

Work carried out within the framework of the AMICI project funded by the Agence Nationale pour la Recherche (ANR-14-CE32-0004-01).

Numerical resources provided by GENCI (project no. 056348), Mésocentre of Aix-Marseille University (project no. b009), EUROfusion (project MaCoToP)

Acknowledgements

GENCI

MESOCENTRE